



Electromechanical Indicators and Controllers




Panel-mounting Thermostats



Designation	1 Panel-mounting thermostat, EM series		2 JUM0 heatTHERM
Approval mark	   DGRL 97/23/EG		   DGRL 97/23/EG
Implemented function to DIN EN 14 597	TR, TW, TB, STW, STB		
Control ranges	–20 to +650 °C		up to 365 °C
Switching differential	optionally 1 %-10 %		optionally 2,5-7 %
Contact rating	16 A, 230V AC		
Switching device	1, 2, 3 or 4 single-pole snap-action switches		single-pole snap-action switch
Measuring system	copper or stainless steel		
Temperature compensation	on request		standard
Further information	data sheet 60.2021		data sheet 60.2031

Surface-mounting Thermostats



Designation	❶ Surface-mounting thermostat, ATH series	❷ Surface-mounting thermostat, heatTHERM-AT/heatTHERM-DR	❸ Explosion-protected surface-mounting thermostat, ATH-Ex series
Approval mark		DIN EN 14 597  DGRL 97/23/EG	
Implemented function to DIN EN 14 597	TR, TW, TB, STW, STB single and twin thermostat	TR, TW, STW, STB single and twin thermostat	TW, TB, STW, STB
Enclosure protection	maximum IP65	maximum IP54	IP65
Control ranges	-20 to +500 °C	-10 to +365 °C	-20 to +500 °C
Switching differential	optionally 1,5 %-9 %	2,5 % or 7 %	3 %, 5 % or 6 %
Contact rating	10 A, 230 V AC	16 A, 230 V AC	5 A, 230 V AC, 16 A, 230 V AC
Switching device	single-pole snap-action switch		
Measuring system	copper or stainless steel		
Special features	with rigid stem or capillary	„Push-In®“ Connection circuit, Ambient temperature compensation with rigid stem	for potentially explosive gas atmospheres, Zone 1 and potentially explosive atmospheres, Zone 21
Further information	data sheets 60.3021, 60.3026	data sheet 60.3070	data sheets 60.5041, 60.5051

„Push In®“ terminal system: patented connection technology from Weidmüller GmbH & Co. KG, Detmold, Germany

Digital Indicator



Bimetal Temperature Switch



Designation	② JUMO dTHERM-M, with integrated 2-wire transmitter	③ Bimetal Temperature Switch
Housing	dia. 100mm, stainless steel	brass or stainless steel
Enclosure protection	IP 65	maximum IP 67
Control ranges	–	40 to 140 °C (steps of 5 K)
Indication range	–50 to 600 °C	–
Switching action	–	break or make contact
Switching differential	–	depending on switch temperature
Controller output	4 to 20 mA	–
Contact rating	–	10 A, 230 V AC, p.f. = 1
Probe input	Pt100 resistance thermometer	–
Measuring circuit monitoring	break and short-circuit	–
Supply	DC 12 – 30 V	–
Further information	data sheet 60.8624	data sheet 60.8301

Indicators




Type	❶ Bimetal dial thermometer standard version, industrial version, chemical plant version	❷ Dial thermometer	❸ Dial thermometer	❹ Dial thermometer
Class	1 and 1.5	1.5	2	1
Enclosure protection	maximum IP 65		IP53 at front	IP 65
Meas. range	-50 to +500 °C	-40 to +600 °C	-40...+350 °C	-40...+500 °C
Housing	zinc-plated sheet steel, or stainless steel	stainless steel 1.4301, with ring seam	black ABS plastic	stainless steel (1.4301) with bayonet connection
Housing sizes (round)	dia. 50, 63, 80, 100, 160 mm	dia. 60, 80, 100 mm	dia. 52, 60 mm	dia. 100, 160 mm
Housing sizes (square)	-	72 mm x 72 mm, 96 mm x 96 mm	48 mm x 48 mm, 52 mm x 52 mm, 72 mm x 72 mm	-
Style	surface-mounting instrument with rigid immersion tube, tube exit central or downwards	as panel- or surface- mounting instrument, rigid immersion tube	panel-mounting instrument with capillary	panel- or surface- mounting instrument, with capillary or rigid immersion tube
Further information	data sheets 60.8001, 60.8002, 60.8003	data sheet 60.8201	data sheet 60.8202	data sheet 60.8225

Controllers



1

2



3



Type	❶ Contact dial thermometer	❷ MICROSTAT-M/M1	❸ Contact dial thermometer transformer version
Class	1	2	1.5
Enclosure protection	IP 65	IP 53 at front	IP 54
Meas. range	–40 to +500 °C	–40 to +600 °C	–20 to +120 °C
Contacts	maximum 3 contacts	1 or 2 microswitches	1 or 2 microswitches with drag pointer
Contact rating	18VA or 50VA at 230V AC/DC	5A or 10A at 230V AC	
Housing (round)	stainless steel (1.4301) with bayonet connection	black ABS plastic or galvanized sheet steel	plastic (PA 6) UV stabilized, fiberglass enforced
Housing (square)	galvanized sheet steel	–	
Housing sizes (round)	dia. 100, 160 mm	dia. 60, 80, 100 mm	dia. 80 mm
Housing sizes (square)	96 mm x 96 mm	72 mm x 72 mm, 96 mm x 96 mm	–
Style	panel- or surface-mounting instrument, with capillary or rigid immersion tube	panel-mounting instrument with capillary	surface-mounting instrument, with capillary or rigid immersion tube
Further information	data sheet 60.8425	data sheets 60.8501	data sheet 60.8540


Outstanding quality for the global market




<http://brochures.jumo.info>




PR 00038 EN




PR 00058 EN




PR 00062 EN




PR 00056 EN




PR 00059 EN



PR 00063 EN



PR 00057 EN



PR 00061 EN



PR 40023 EN

2010-06-02/00461168

www.jumo.net