

Compact pH Measuring Instruments With Pro Engineering

With interchangeable measurement electrode



pH

°C

The new pH measuring instruments with innovative probe engineering



pH1 probe head for liquids

Measurement of the pH value plays an important role in many areas. Anywhere where there are chemical and biochemical reactions, the pH value has an important indicator function.

Even though the engineering has been established on the market for years, there are still some application problems:

- Short life span of pH probes due to glass breakage and dirt ingress, for example
- Sensitivity to dirt of the pH probe resulting in incorrect measurements
- Spillage of storage solution
- Handling problems when calibrating
- Lack of one-hand penetration pH probes for liquid and viscoplastic substances
- Lack of combined temperature and pH measurement



pH2 probe head for semisolid substances

Together with experts from industry and the trades, Testo has developed innovative solutions.

Instead of a liquid electrolyte, Testo pH probes have a gel electrolyte as a reference substance for pH measurement which facilitates the use of a hole diaphragm between the measurement electrode and housing in place of the micro-porous structure usually used in pH probes. The micro-porous structure becomes blocked up more quickly, similar to a finely woven sieve, consequently requiring regular service which in return results in a shorter life.

Due to the large volume of gel electrolyte and the hole diaphragm, Testo pH probes are not only leakproof, they are almost completely maintenance-free, robust and unaffected by dirt and dust.

The combination of the pH penetration tip and temperature probe in a one-hand instrument for accurate and fast temperature compensation is unique. Consequently, accurate readings are guaranteed in all ambient conditions.

With the development of different, breakproof probe geometries, Testo is making available special solutions for liquid as well as for viscoplastic substances.

The leakproof storage solution is also new.

pH probes must be stored in moist conditions, when not in use, in order to prevent the glass membrane coating around the measurement electrode and the diaphragm from drying out. Pure water alone should not be used since water would release the conducting components contained in the probe electrolytes. A potassium chloride solution is usually used for this purpose. As with every liquid, it can leak which, particularly in the food branch, can lead to contamination of raw foodstuffs or products.

Testo, with its new gel storage, has eliminated this disadvantage. The potassium chloride solution is available in a container in gel form. What doesn't drip can't leak!



Interchangeable probe



The potassium chloride solution bonded in the gel cannot leak.



Fast and convenient measurement during production



pH tip embedded in break-proof plastic



Set case with testo 205, pH 4.0 and 7.0 buffers as well as storage cap



pH buffer solution in the storage bottle with dosing container

The professional pH measuring instrument for the food sector

testo 205 is a pH measuring instrument, developed together with experts from the food sector, for measurements in viscoplastic materials. Its main application is to be found in meat processing. Its ergonomic design and its surface display make the testo 205 ideal for applications in production, Incoming goods and for recurring measurements. The combination of the pH penetration tip and the temperature probe for fast and accurate temperature compensation is unique. Automatic recognition of a stable reading makes the whole measurement process much easier.

Your benefits

- Combined penetration tip with temperature probe
- Measurement tip can be changed by user
- Maintenance-free gel electrode
- Backlit display
- Audible button feedback
- 2 line display
- Automatic full scale value recognition
- 1, 2, or 3 point calibration possible

Complete case for field use

All of the required accessories are clearly arranged in the high-quality aluminium case together with the testo 205 measuring instrument. The containers with the buffer solutions can be set up in the case so that calibration can be carried out on site.

Set contents

- testo 205
- pH buffer 4 and 7 (each 250 ml)
- Gel storage cap
- Instruction manual
- Batteries



Robust food penetration pH/C° measuring instrument with automatic temperature compensation

Technical data

Instrument	testo 205
Parameters	pH / °C
Sensor	pH electrode / NTC
Number of meas. channels	2
Meas. range	0 to 14 pH 0 to 60 °C (Short-term to +80 °C max. 5 min)
Resolution	0.01 pH 0.1 °C
Accuracy	±0.02 pH ±0.4 °C
Temperature compensation	Automatic
Display	LCD, 2 lines
Probes	Screw-in pH / °C probe modules
Measurement rate	2 measurements per second
Oper. temp.	0 to +50 °C
Storage temp.	-20 to +70 °C
Battery type	4x lithium button cell LR44
Battery life	80 h (Auto Off 10 Min)
Material/Housing	ABS with soft coating in handle area, protection class IP 65
Dimensions	145 x 38 x 167 mm
Weight	135 g

testo 206-pH1 / pH2 / pH3 – Versatile pocket-size pH sticks



pH1 probe head for liquids



pH2 probe head for semisolid materials



pH3 probe head with BNC interface

Benefits

testo 206 pH1 and pH2

- Insensitive to dirt on account of hole diaphragm and gel reference electrolyte
- Large volume of gel reference electrolyte guarantees a long life
- No maintenance necessary. No need to fill up electrolyte solution.
- So versatile it can be used for nearly all applications:
 - for materials containing protein
 - highly contaminated solutions can be measured
- Low membrane resistance results in fast and stable readings
- Unique design makes breakage practically impossible
- Combination: pH measurement sensor with temperature measurement probe

testo 206 pH3

- Connection of all external probes with BNC plug
- Automatic and manual temperature compensation possible

testo 206 pH1, pH2 and pH3

- The instrument is also suitable for outdoor applications or for tough industrial conditions thanks to the "TopSafe" protection case included.
- 2 line display
- Automatic full scale value recognition
- 1, 2 or 3 point calibration possible

Technical data

Instrument	testo 206-pH1 and pH2
Parameters	pH / °C
Sensor	pH electrode / NTC
Number of meas. channels	2 channel
Meas. range	0 to 14 pH 0 to 60 °C (Short-term to +80 °C max. 5 min)
Resolution	0.01 pH 0.1 °C
Accuracy	±0.02 pH ±0.4 °C
Temp. compensation	Automatic
Display	LCD, 2 lines
Probes	Screw-in pH / °C probe modules
Measurement rate	2 measurements per second
Oper. temp.	0 to +60 °C
Storage temp.	-20 to +70 °C
Battery type	1x CR2032
Battery life	80 h (Auto Off 10 min)
Material/Housing	ABS with TopSafe, protection class IP 68
Dimensions	197 x 33 x 20 mm
Weight (testo 206 pH1) (testo 206-pH2)	69 g 62 g

Technical Data for testo 206-pH3:

Refer to the data sheet of the respective probe for pH and temperature accuracy.

testo 206-pH1, compact pH tester for liquids



testo 206-pH1 is ideal for measurements in liquids



The "TopSafe" case protects in tough industrial conditions

testo 206-pH1, compact pH tester for liquids

Compact pH measuring instrument for measuring liquids. Built-in temperature probe for efficient temperature compensation. Automatic recognition of a stable reading makes it easier to measure. The "TopSafe" case included makes the instrument ideal for outdoor applications or for use in tough industrial conditions.

Your benefits

- Versatile, accurate pH measuring instrument
- Not affected by dust or dirt thanks to the TopSafe protection case
- Maintenance-free gel electrode
- Built-in temperature probe
- 2 line display
- Automatic full scale value recognition
- 1, 2, or 3 point calibration possible

testo 206-pH1 applications

- pH measurement in the environmental sector (water, waste water,...)
- Condensate neutralisation (heating engineering/condensing boilers)
- pH applications in the industrial sector (e.g. pH value of lubricants)
- pH measurement in the food sector (e.g. fruit juice production)
- Generally: Liquids in all sectors

testo 206-pH1 instrument set



One-hand pH/°C measuring instrument, pH1 probe head for liquids, storage cap with gel, TopSafe and belt/wall holder

Part no. 0563 2061

testo 206-pH1 Starter Set



One-hand pH/°C measuring instrument, pH1 probe head for liquids, storage cap with gel, calibration dosing bottles 250 ml pH 4+7, TopSafe, belt/wall holder and aluminium case

Part no. 0563 2065

testo 206-pH2, compact pH tester for viscoplastic substances



Automatic full scale value recognition and clear 2 line display.

testo 206-pH2, compact pH tester for viscoplastic substances

testo 206-pH2 is the pH measuring instrument for measurements in viscoplastic materials, such as jelly, creams, meat, cheese, marmelade and fruit. The combination of a pH penetration tip and temperature probe for efficient temperature compensation is unique. Automatic recognition of a stable reading makes the whole measurement process easier. The "TopSafe" case supplied makes the instrument ideal for outdoor applications and for use in tough industrial conditions.

testo 206-pH2 applications

- Milk and milk products (yoghurt, cheese, ...)
- pH value of mash during the production of spirits
- pH value during food production (e.g. salad dressing)
- Applications in the cosmetics sector (cream production)
- pH monitoring during meat processing

Your benefits

- Compact pH measuring instrument with penetration tip
- Not affected by dirt and dust thanks to TopSafe protection case
- Maintenance-free gel electrode
- Automatic full scale value recognition
- Built-in temperature probe
- 2 line display
- 1, 2, or 3 point calibration possible



testo 206-pH2 is ideal for measurements in viscoplastic substances.

testo 206-pH2 Instruments Set



One-hand pH/°C measuring instrument, pH2 probe head for viscoplastic substances, storage cap with gel, TopSafe and belt/wall holder

Part no. 0563 2062

testo 206-pH2 Starter Set



One-hand pH/°C measuring instrument, pH2 probe head for viscoplastic substances, storage cap with gel, calibration dosing bottles 250 ml pH 4+7, TopSafe, belt/wall holder and aluminium case

Part no. 0563 2066

testo 206-pH3, compact pH tester to connect external probes



testo 206-pH3 facilitates the connection of external pH probes

testo 206-pH3, pH tester for connecting external probes

testo 206-pH3 is equipped with a BNC socket which makes it possible to connect all pH probes to the instrument. The temperature value supplied is automatically analysed if Testo pH probes with a built-in temperature sensor are used. In the case of probes without a temperature sensor, the temperature can be set manually. Automatic recognition of a stable reading makes the measurement easier. Thanks to the "TopSafe" protection case, the instrument is ideal for outdoor applications and for use in tough industrial conditions.

Your benefits

- External pH probes can be connected
- Not affected by dirt and dust thanks to the TopSafe protection case
- 2 line display
- Automatic full-scale value recognition
- 1, 2, or 3 point calibration possible

testo 206-pH3 applications

- All of the probes with BNC plugs available on the market can be connected.
- Testo probes with temperature measurement facilitate automatic temperature compensation.
- Ideal for pH measurements in the lab
- pH monitoring in the environmental sector (water quality, earth samples)
- pH monitoring in the industrial sector (e.g. photo processing vats)



Automatic temperature compensation in external probes with temperature sensor

Instrument Set testo 206-pH3



One-hand pH/°C measuring instrument, pH3 probe head with BNC interface, TopSafe and belt/wall holder

Part no. 0563 2063

testo 206-pH3 Versatile Set



One-hand pH/°C measuring instrument, pH3 probe head with BNC interface, pH probe Type 14, storage cap with gel, calibration dosing bottles 250 ml pH 4+7, TopSafe, belt/wall holder and aluminium case

Part no. 0563 2068

testo 206 pH3 – Affordable Set



One-hand pH/°C meter, pH3 probe head with BNC interface, pH probe Type 01, Storage cap with gel, calibration dosing bottles 250 ml pH 4+7, TopSafe, belt/wall holder and aluminium case

Part no. 0563 2067

Ordering data

Qty.	Instruments	Part no.
	testo 205 Starter Set: pH measuring instrument with penetration probe, gel storage cap, wall holder, pH4 buffer (250 ml), pH 7 buffer (250 ml) in an aluminium case	0563 2052
	testo 205 Instruments Set: pH measuring instrument with penetration probe, gel storage cap and wall holder	0563 2051
	testo 206-pH1 Starter Set - One-hand pH/°C measuring instrument, pH1 probe head for liquids, storage cap with gel, calibration dosing bottles 250 ml pH 4+7, TopSafe, belt/wall holder and aluminium case	0563 2065
	testo 206-pH1 Instruments Set - One-hand pH/°C measuring instrument, pH1 probe head for liquids, storage cap with gel, TopSafe and belt/wall holder	0563 2061
	testo 206-pH2 Starter Set - One-hand pH/°C measuring instrument, pH2 probe head for viscoplastic substances, storage cap with gel, calibration dosing bottles 250 ml pH 4+7, TopSafe, belt/wall holder and aluminium case	0563 2066
	testo 206-pH2 Instruments Set - One-hand pH/°C measuring instrument, pH2 probe head for viscoplastic substances, storage cap with gel, TopSafe and belt/wall holder	0563 2062
	Instrument Set testo 206-pH3 - One-hand pH/°C measuring instrument, pH3 probe head with BNC interface, TopSafe and belt/wall holder	0563 2063
	testo 206 pH3 - Affordable Set - One-hand pH/°C meter, pH3 probe head with BNC interface, pH probe Type 01, Storage cap with gel, calibration dosing bottles 250 ml pH 4+7, TopSafe, belt/wall holder and aluminium case	0563 2067
	testo 206-pH3 Versatile Set - One-hand pH/°C measuring instrument, pH3 probe head with BNC interface, pH probe Type 14, storage cap with gel, calibration dosing bottles 250 ml pH 4+7, TopSafe, belt/wall holder and aluminium case	0563 2068

Qty.	Accessories	Part no.
	Spare pH probe for testo 205 with gel storage cap	0650 2051
	Spare pH probe for testo 206 incl. gel storage cap	0650 2061
	Spare pH probe pH2 for testo 206 incl. gel storage cap	0650 2062
	Spare probe Type 01 for testo 206-pH3, incl. gel storage cap	0650 2063
	Spare probe Type 14 for testo 206-pH3, incl. gel storage cap	0650 2064
	Storage cap for testo 205 with KCL gel filling	0554 2051
	Storage cap for testo 205 with KCl gel filling (pack of 3)	0554 2052
	Storage cap for testo 206 with KCl gel filling	0554 2067
	Storage cap for testo 206 with KCl gel filling (pack of 3)	0554 2068
	pH buffer solution 4.01 in dosing bottle (250 ml), with DKD calibration certificate	0554 2061
	pH buffer solution 4.01 in dosing bottle (3 x 250 ml per pack), with DKD calibration certificate	0554 2062
	pH buffer solution 7.00 in dosing bottle (250 ml), with DKD calibration certificate	0554 2063
	pH buffer solution 7.00 in dosing bottle (3 x 250 ml per pack), with DKD calibration certificate	0554 2064
	pH buffer solution 10.01 in dosing bottle (250 ml), with DKD calibration certificate	0554 2065
	pH buffer solution 10.01 in dosing bottle (3 x 250 ml per pack), with DKD calibration certificate	0554 2066

testo 230, The Classic in the Compact Class



testo 230 combines a complete pH measuring instrument and a high standard thermometer in a compact, waterproof housing. The redox voltage can also be determined by connecting the redox electrode type 06.

The instrument has automatic temperature compensation and can be calibrated in the pH range with standard and also with DIN buffers.

Part no. 0560 2304

For more detailed information about testo 230, please send for the "pH measuring instrument plus thermometer" (Part no. 0981 3434).

To:

Sender	
Name	Address
Company	City
Telephone/Fax	Email
Department	Date, Signature

Subject to change without notice.